

DECLARATION OF PERFORMANCE (ZER0.3 5Plus)

No DOP005PAN

1. Unique identification code of the product-type

Dry-pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$.

2. Intended use

Ceramic tiles for internal flooring and internal and external wall applications, pre-assembled on a fibreglass mesh.

3. Name and contact address of the manufacturer

PANARIA CERAMICA, via Panaria Bassa 22/a, 41034 Finale Emilia (MO) – ITALY

4. System of assessment and verification of constancy of performance of the construction products (AVCP)

System 4

5. Name and identification number of notified body, if applicable

Not applicable

6. Declared performance

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	A2 _{fl} -s1/A2-s1,d0	 EN 14411:2012
Release of dangerous substances		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	≥ 700 N	
Modulus of rupture	≥ 35 N/mm ²	
Slip resistance	See Annex enclosed	
Tactility	NPD	
Adhesion resistance		
- Cementitious adhesive C1 class	NPD	
- Cementitious adhesive C2 class	NPD	
Thermal shock resistance	Passed	
Durability		
- Internal use	Passed	
- External use: Frost resistance	Passed	

7. The performance of the product identified in point 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued, under the sole responsibility of the manufacturer identified in point 3.

Finale Emilia, Aprile 03, 2025

Signed for and on behalf of the manufacturer by



Marco Levoni, Panaria Ceramica Quality Dept.

Annex to the Declaration Of Performance N. DOP005PAN

Slip resistance			
Series	Products	DIN EN 16165 Annex B	BCRA D.M. 236/1989
ZERO.3 Must 5Plus	Be White Lux Plus 5,5 mm, Be Black Lux Plus 5,5 mm, Be White Soft Plus 5,5 mm, Be Black Soft Plus 5,5	NPD	NPD
ZERO.3 Prime Stone 5Plus	White Prime Soft Plus 5,5 mm, Silver Prime Soft Plus 5,5 mm, Sand Prime Soft Plus 5,5 mm, Greige Prime Soft Plus 5,5 mm, Black Prime Soft Plus 5,5 mm	R9	>0,40
ZERO.3 Trilogy 5Plus	Calacatta White Soft Plus 5,5 mm, Onyx Light Soft Plus 5,5 mm, Moon Beige Soft Plus 5,5 mm, Sandy Grey Soft Plus 5,5 mm, Sky Smoke Soft Plus 5,5 mm	NPD	NPD
ZERO.3 Trilogy 5Plus	Calacatta White Lux Plus 5,5 mm, Onyx Light Lux Plus 5,5 mm, Moon Beige Lux Plus 5,5 mm, Sandy Grey Lux Plus 5,5 mm, Sky Smoke Lux Plus 5,5 mm	NPD	NPD