

DECLARATION OF PERFORMANCE (ZER0.3 6mm)

No DOP006PAN

1. Unique identification code of the product-type

Dry-pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$.

2. Intended use

Ceramic tiles for internal flooring and internal and external wall applications.

3. Name and contact address of the manufacturer

PANARIA CERAMICA, via Panaria Bassa 22/a, 41034 Finale Emilia (MO) – ITALY

4. System of assessment and verification of constancy of performance of the construction products (AVCP)

System 4

5. Name and identification number of notified body, if applicable

Not applicable

6. Declared performance

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	A1 _{fl} /A1	 EN 14411:2012
Release of dangerous substances		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	≥ 700 N	
Modulus of rupture	≥ 35 N/mm ²	
Slip resistance	See Annex enclosed	
Tactility	NPD	
Adhesion resistance		
- Cementitious adhesive C1 class	NPD	
- Cementitious adhesive C2 class	NPD	
Thermal shock resistance	Passed	
Durability		
- Internal use	Passed	
- External use: Frost resistance	Passed	

7. The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Finale Emilia, April 03, 2025

Signed for and on behalf of the manufacturer by



Marco Levoni, Panaria Ceramica Quality Dept.

PANARIA CERAMICA – Via Panaria Bassa, 22/a – 41034 Finale Emilia (MO) Italy – email info@panaria.it – www.panaria.it

Tel. +39 0535 95111 - Fax +39 0535 95111 90503 - Fax (amm.) +39 0535 95244 - Fax (comm. Italia) +39 0535 95263 - Fax (comm. Europe) +39 0535 95254
Panariagroup Industrie Ceramiche S.p.A. - Sede Legale: Via Panaria Bassa 22/a - 41034 FINALE EMILIA (Modena) Italy - Capitale Sociale Euro 22.677.645,50 Int.Vers. - R.E.A.
248427 Partita I.V.A., CF e Iscrizione al Registro Imprese di Modena n. 01865640369
Pag. 1/2

Annex to the Declaration Of Performance N. DOP006PAN

Slip resistance			
Series	Products	DIN EN 16165 Annex B	BCRA D.M. 236/1989
ZERO.3 Context 6mm	Square, Loft, Store, Hangar, Mansion	R10	>0,40
ZERO.3 Eternity 6mm	Statuario White Lux, Arabesque Pearl Lux, Breach Grey Lux, Marquina Black Lux	NPD	NPD
ZERO.3 Eternity 6mm	Statuario White Soft, Arabesque Pearl Soft, Breach Grey Soft, Marquina Black Soft	NPD	NPD
ZERO.3 Perpetual Soft	Venato Gold Soft, Breccia Warm Soft, Onice Clear Soft, Orobico Blend Soft, Belvedere Dark Soft	NPD	NPD
ZERO.3 Perpetual Lux	Venato Gold Lux, Breccia Warm Lux, Onice Clear Lux, Orobico Blend Lux, Belvedere Dark Lux	NPD	NPD
ZERO.3 Stone Trace 6mm	Glade, Creek, Crest, Hollow, Abyss	R10	>0,40